

**Technical Specifications**
**OPERATING DATA**

|                      |          |
|----------------------|----------|
| Payload              | 3.100 kg |
| Skip level capacity  | 1.300 l  |
| Skip heaped capacity | 1.690 l  |
| Skip water capacity  | 855 l    |
| Skip rotation        | +/-90°   |

**POWER UNIT DATA**

|                      |            |
|----------------------|------------|
| Engine manufacturer  | Yanmar     |
| Engine model         | 4TNV88     |
| Engine maximum power | 35,5 kW    |
| Standard emission    | EU Stage V |
| Displacement         | 2.190 cc   |
| Engine speed         | 3.000 rpm  |

**TRANSMISSION DATA**

|                           |  |
|---------------------------|--|
| Traction                  | AWD  |
| Transmission manufacturer | Bosch-Rexroth                              |
| Transmission              | Hydrostatic with mechanical distribution - |
| Hydrostatic pump          | Axial piston - 40 cc/rev                   |
| Hydrostatic motor         | Bent axis - 80 cc/rev                      |
| Operating pressure        | 400 bar                                    |

**VEHICLE PERFORMANCE**

|                                   |          |
|-----------------------------------|----------|
| Maximum speed                     | 28 km/h  |
| Max. slope under full load        | 50%      |
| Steering angle                    | +/- 35°  |
| Steering radius (average radius)  | 2.870 mm |
| Lock to lock steering wheel turns | 4,26     |
| Twist angle                       | 10°      |

**PNEUMATICS**

|                        |              |
|------------------------|--------------|
| Agro-industrial 14-ply | 10.0/75-15.3 |
|------------------------|--------------|

**Dimensions 1/2**

